

SFF specifications are available at <http://www.snia.org/sff/specifications>.



SFF-9482

Reference Guide for

Serial Attachment 2X Unshielded Connector Pinouts

Rev 1.0

July 18, 2018

Secretariat: SFF TA TWG

Abstract: This specification is a guide to the pinout usage of the SFF-8482 two lane, high speed plug and receptacle connector that is designed for use as a connector system supporting SAS devices.

This specification provides a common reference for systems manufacturers, system integrators, and suppliers.

This specification is made available for public review, and written comments are solicited from readers. Comments received by the members will be considered for inclusion in future revisions of this specification.

The description of a connector in this specification does not assure that the specific component is actually available from connector suppliers. If such a connector is supplied it must comply with this specification to achieve interoperability between suppliers.

POINTS OF CONTACT:

Jay Neer
Molex LLC
2222 Wellington Ct
Lisle, IL 60532
Ph: 561-447-2907
Email: jay.neer@molex.com

Chairman SFF TA TWG
Email: SFF-Chair@snia.org

Intellectual Property

The user's attention is called to the possibility that implementation of this Specification may require the use of an invention covered by patent rights. By distribution of this specification, no position is taken with respect to the validity of a claim or claims or of any patent rights in connection therewith. This specification is considered SNIA Architecture and is covered by the SNIA IP Policy and as a result goes through a request for disclosure when it is published. Additional information can be found at the following locations:

- Results of IP Disclosures: <http://www.snia.org/sffdisclosures>
- SNIA IP Policy: <http://www.snia.org/ippolicy>

Change History

Revision 0.1 (November 27, 2012)

- First draft of SFF-9680

Revision 0.2 (May 8, 2015)

- Title/number change (contents of SFF-8680 merged into SFF-8482)

Revision 1.0 (July 18, 2018)

- Upgraded to SNIA template
- Replaced "Reference Guide" with "Published" in header
- Added "Reference" watermark

REFERENCE

Foreword

The development work on this specification was done by the SNIA SFF TWG, an industry group. Since its formation as the SFF Committee in August 1990, the membership has included a mix of companies which are leaders across the industry.

When 2 1/2" diameter disk drives were introduced, there was no commonality on external dimensions e.g. physical size, mounting locations, connector type, connector location, between vendors. The SFF Committee provided a forum for system integrators and vendors to define the form factor of disk drives.

During their definition, other activities were suggested because participants in SFF faced more challenges than the form factors. In November 1992, the charter was expanded to address any issues of general interest and concern to the storage industry. The SFF Committee became a forum for resolving industry issues that are either not addressed by the standards process or need an immediate solution.

In July 2016, the SFF Committee transitioned to SNIA (Storage Networking Industry Association), as a TA (Technology Affiliate) TWG (Technical Work Group).

Industry consensus is not a requirement to publish a specification because it is recognized that in an emerging product area, there is room for more than one approach. By making the documentation on competing proposals available, an integrator can examine the alternatives available and select the product that is felt to be most suitable.

SFF meets during the T10 (see www.t10.org) and T11 (see www.t11.org) weeks, and SSWGs (Specific Subject Working Groups) are held at the convenience of the participants.

Many of the specifications developed by SFF have either been incorporated into standards or adopted as standards by ANSI, EIA, JEDEC and SAE.

For those who wish to participate in the activities of the SFF TWG, the signup for membership can be found at:

<http://www.snia.org/sff/join>

The complete list of SFF Specifications which have been completed or are currently being worked on by the SFF Committee can be found at:

<http://www.snia.org/sff/specifications>

Suggestions for improvement of this specification will be welcome, they should be submitted to:

<http://www.snia.org/feedback>

CONTENTS

| | |
|---------------------------|---|
| 1. Scope | 5 |
| 1.1 Copyright | 5 |
| 1.2 Disclaimer | 5 |
| 2. References | 5 |
| 2.1 Sources | 5 |
| 2.2 Conventions | 5 |
| 3. General Description | 6 |
| 4. Connector Usage Models | 6 |

REFERENCE

1. Scope

This specification defines pinouts used with the SFF-8482 Serial Attachment 2X Unshielded Connector.

1.1 Copyright

The SNIA hereby grants permission for individuals to use this document for personal use only, and for corporations and other business entities to use this document for internal use only (including internal copying, distribution, and display) provided that:

1. Any text, diagram, chart, table or definition reproduced shall be reproduced in its entirety with no alteration, and,
2. Any document, printed or electronic, in which material from this document (or any portion hereof) is reproduced shall acknowledge the SNIA copyright on that material, and shall credit the SNIA for granting permission for its reuse.

Other than as explicitly provided above, there may be no commercial use of this document, or sale of any part, or this entire document, or distribution of this document to third parties. All rights not explicitly granted are expressly reserved to SNIA.

Permission to use this document for purposes other than those enumerated (Exception) above may be requested by e-mailing copyright_request@snia.org. Please include the identity of the requesting individual and/or company and a brief description of the purpose, nature, and scope of the requested use. Permission for the Exception shall not be unreasonably withheld. It can be assumed permission is granted if the Exception request is not acknowledged within ten (10) business days of SNIA's receipt. Any denial of permission for the Exception shall include an explanation of such refusal.

1.2 Disclaimer

The information contained in this publication is subject to change without notice. The SNIA makes no warranty of any kind with regard to this specification, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. The SNIA shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this specification.

Suggestions for revisions should be directed to <http://www.snia.org/feedback/>.

2. References

2.1 Sources

There are several projects active within the SFF TWG. The complete list of specifications which have been completed or are still being worked on is contained in the document SFF-8000 which can be found at <http://www.snia.org/sff/specifications>.

Copies of ANSI standards may be purchased from the InterNational Committee for Information Technology Standards (<http://www.techstreet.com/incitsgate.tmp1>).

2.2 Conventions

The dimensioning conventions are described in ANSI-Y14.5M, Geometric Dimensioning and Tolerancing. All dimensions are in millimeters, which are the controlling dimensional units (if inches are supplied, they are for guidance only).

The ISO convention of numbering is used i.e., the thousands and higher multiples are separated by a space and a period is used as the decimal point. This is equivalent to the English/American convention of a comma and a period.

| American | French | ISO |
|-------------|-------------|-------------|
| 0.6 | 0,6 | 0.6 |
| 1,000 | 1 000 | 1 000 |
| 1,323,462.9 | 1 323 462,9 | 1 323 462.9 |

3. General Description

When a new SFF connector specification is developed there may be more than one industry interface planning to make use of it. Groups working on interfaces being developed under non-disclosure are unable to compare and discuss anticipated usage.

Pinouts are discussed during connector development and initial definitions assigned to ensure that the connector meets the needs of the interested interfaces.

This specification is a guide to the anticipated pinout usage of the interfaces under development.

4. Connector Usage Models

The pinouts defined in SFF-8639 Multifunction 6X Unshielded Connector Pinouts cover the connector systems defined in SFF-8482 and SFF-8629.

This specification defines a system that may be used to implement the following:

- Single port SATA (as defined by Serial ATA revision 3.1)
- Dual port SAS (as defined by SFF-8482)

The connector system defines a total of 29 contacts.

The receptacle may implement all of the defined contacts while the plug may implement only the contacts required by the use case supported on a particular device.

The connector system may be utilized for use cases not defined in this specification.

Table 4-1 and pins S1-S14 in Table 4-2 of the SFF-9639 specification define the signal utilization.

WARNING: The definitive reference for signals are the using interfaces. Readers should be aware that the tables may not be correct after the interfaces have been defined and distributed for public use.