



SFF-TA-1000

Former Specification for

2.5" Form Factor Drive with High Density Connector

Rev 2.0

November 12, 2021

SECRETARIAT: SFF TA TWG

ABSTRACT: This specification formerly defined the mechanical attributes of the 2.5" form factor drive with high density connector. This form factor differs from previous versions of 2.5" drives in that it only has side mounting holes rather than both side and bottom mounting holes and defines the location of a high density connector that provides power, sideband signals, and up to eight or sixteen high speed data lanes.

REASON FOR EXPIRATION: Obsolete

This specification is no longer relevant to the industry because this form factor was not implemented.

POINTS OF CONTACT:

Alvin Cox
Seagate Technology, LLC
7725 W Reno Ave #334
Oklahoma City, OK 73127
Ph: 405-206-4809
Email: alvin.cox@seagate.com

Chairman SFF TA TWG
Email: SFF-Chair@snia.org

SFF specifications are available at <http://www.snia.org/sff/specifications>



SFF-TA-1000

Specification for

2.5" Form Factor Drive with High Density Connector

Rev 1.0

January 19, 2018

Secretariat: SFF TA TWG

Abstract: This specification defines the mechanical attributes of the 2.5" form factor drive with high density connector.

This form factor differs from previous versions of 2.5" drives in that it only has side mounting holes rather than both side and bottom mounting holes and defines the location of a high density connector that provides power, sideband signals, and up to eight high speed data lanes.

This specification provides a common reference for systems manufacturers, system integrators, and suppliers.

This specification is made available for public review, and written comments are solicited from readers. Comments received by the members will be considered for inclusion in future revisions of this specification.

The description of the device in this specification does not assure that the specific component is actually available from suppliers. If such a device is supplied it must comply with this specification to achieve interoperability between suppliers.

POINTS OF CONTACT:

Alvin Cox
Seagate Technology
7725 W Reno Ave #334
Oklahoma City, OK 73127
Ph: 405-206-4809
Email: alvin.cox@seagate.com

Chairman SFF TA TWG
Email: SFF-Chair@snia.org

Intellectual Property

The user's attention is called to the possibility that implementation of this Specification may require the use of an invention covered by patent rights. By distribution of this specification, no position is taken with respect to the validity of a claim or claims or of any patent rights in connection therewith. This specification is considered SNIA Architecture and is covered by the SNIA IP Policy and as a result goes through a request for disclosure when it is published. Additional information can be found at the following locations:

- Results of IP Disclosures: <http://www.snia.org/sffdisclosures>
- SNIA IP Policy: <http://www.snia.org/ippolicy>

Change History

- Rev 0.1.0 R0001 March 13, 2017
- Initial release.
- Rev 0.1.0 R0002 April 27, 2017
- Changed dimensions to relocate main PCB. (A10, A23)
 - Corrected revision number
- Rev 0.1.1 November 3, 2017
- Corrected revision number.
 - Removed LED requirement.
 - Relocated connector.
 - Changed connector opening to minimum instead of tolerance.
 - Added lead in requirement for mounting holes.
 - Clarified mounting screw penetration.
 - Updated figures.
- Rev 0.1.2 December 20, 2017
- Updated SFF-8000 links.
 - Updated Figure 3-2 title.
- Rev 1.0 January 19, 2018
- Initial publication.

Foreword

The development work on this specification was done by the SNIA SFF TWG, an industry group. Since its formation as the SFF Committee in August 1990, the membership has included a mix of companies which are leaders across the industry.

When 2 1/2" diameter disk drives were introduced, there was no commonality on external dimensions e.g. physical size, mounting locations, connector type, connector location, between vendors. The SFF Committee provided a forum for system integrators and vendors to define the form factor of disk drives.

During their definition, other activities were suggested because participants in SFF faced more challenges than the form factors. In November 1992, the charter was expanded to address any issues of general interest and concern to the storage industry. The SFF Committee became a forum for resolving industry issues that are either not addressed by the standards process or need an immediate solution.

In July 2016, the SFF Committee transitioned to SNIA (Storage Networking Industry Association), as a TA (Technology Affiliate) TWG (Technical Work Group).

Industry consensus is not a requirement to publish a specification because it is recognized that in an emerging product area, there is room for more than one approach. By making the documentation on competing proposals available, an integrator can examine the alternatives available and select the product that is felt to be most suitable.

SFF meets during the T10 (see www.t10.org) and T11 (see www.t11.org) weeks, and SSWGs (Specific Subject Working Groups) are held at the convenience of the participants. Material presented to SFF becomes public domain, and there are no restrictions on the open mailing of the presented material by Members.

Many of the specifications developed by SFF have either been incorporated into standards or adopted as standards by ANSI, EIA, JEDEC and SAE.

For those who wish to participate in the activities of the SFF TWG, the sign up for membership can be found at:

<http://www.snia.org/sff/join>

The complete list of SFF Specifications which have been completed or are currently being worked on by the SFF Committee is contained in the document SFF-8000 which can be found at:

<http://www.snia.org/sff/specifications>

Suggestions for improvement of this specification will be welcome, they should be submitted to:

<http://www.snia.org/feedback>

CONTENTS

1.	Scope	6
1.1	Application Specific Criteria	6
1.2	Copyright	6
1.3	Disclaimer	6
2.	References	7
2.1	Industry Documents	7
2.2	Sources	7
2.3	Conventions	7
2.4	Definitions	7
3.	General Description	8

FIGURES

Figure 3-1	2.5" Form Factor Drive with SFF-8631 Connector	10
Figure 3-2	SFF-8631 Connector Location Details on the 2.5" Form Factor	11

TABLES

Table 3-1	2.5" Form Factor Drive with SFF-8631 Connector Dimensions	9
-----------	---	---

1. Scope

This specification defines the mechanical attributes of the 2.5" form factor drive with high density connector.

1.1 Application Specific Criteria

This 2.5" drive form factor provides external dimensions, connector, connector placement, and mounting holes to assist manufacturers in the systems integration of this form factor.

The environment for the 2.5" Drive Form Factor with High Density Connector is a computer, cabinet, or enclosure connecting to one or more drives in a restricted packaging environment.

1.2 Copyright

The SNIA hereby grants permission for individuals to use this document for personal use only, and for corporations and other business entities to use this document for internal use only (including internal copying, distribution, and display) provided that:

1. Any text, diagram, chart, table or definition reproduced shall be reproduced in its entirety with no alteration, and,
2. Any document, printed or electronic, in which material from this document (or any portion hereof) is reproduced shall acknowledge the SNIA copyright on that material, and shall credit the SNIA for granting permission for its reuse.

Other than as explicitly provided above, there may be no commercial use of this document, or sale of any part, or this entire document, or distribution of this document to third parties. All rights not explicitly granted are expressly reserved to SNIA.

Permission to use this document for purposes other than those enumerated (Exception) above may be requested by e-mailing copyright_request@snia.org. Please include the identity of the requesting individual and/or company and a brief description of the purpose, nature, and scope of the requested use. Permission for the Exception shall not be unreasonably withheld. It can be assumed permission is granted if the Exception request is not acknowledged within ten (10) business days of SNIA's receipt. Any denial of permission for the Exception shall include an explanation of such refusal.

1.3 Disclaimer

The information contained in this publication is subject to change without notice. The SNIA makes no warranty of any kind with regard to this specification, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. The SNIA shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this specification.

Suggestions for revisions should be directed to <http://www.snia.org/feedback/>

2. References

2.1 Industry Documents

- ANSI-Y14.5, Geometric Dimensioning and Tolerancing
- SFF-8531 3.5" Form Factor Drive with High Density Connector
- SFF-8631 Serial Attachment X8/X16 Unshielded Device Connector
- SFF-8667 Module with High Density Connector for Enclosure Applications

2.2 Sources

There are several projects active within the SFF Committee. The complete list of specifications which have been completed or are still being worked on are listed in the specification at

<https://ta.snia.org/higherlogic/ws/public/download/1211/latest/SFF-8000.xlsx>.

Copies of ANSI standards may be purchased from the InterNational Committee for Information Technology Standards (<http://www.techstreet.com/incitsgate.html>).

2.3 Conventions

The dimensioning conventions are described in ANSI-Y14.5, Geometric Dimensioning and Tolerancing. All dimensions are in millimeters, which are the controlling dimensional units (if inches are supplied, they are for guidance only).

The ISO convention of numbering is used i.e., the thousands and higher multiples are separated by a space and a period is used as the decimal point. This is equivalent to the English/American convention of a comma and a period.

American	French	ISO
0.6	0,6	0.6
1,000	1 000	1 000
1,323,462.9	1 323 462,9	1 323 462.9

2.4 Definitions

For the purpose of SFF Specifications, the following definitions apply:

Height: The vertical distance from the bottom surface to the farthest overall drive feature.

3. General Description

SFF-TA-1000 defines the location of the SFF-8631 connector on a 2.5" drive form factor that has mounting holes located on the sides and no mounting holes on the bottom.

This specification defines a drive that may be directly inserted into the backplane of a cabinet, without the need for a cable, and provides information necessary to assist manufacturers in the systems integration of small form factor drives. This specification allows only one location for the interface connector on the drive.

Provision exists in the SFF-8631 connector for improved mating via guides. Staggered pin lengths incorporate provision for mating ground prior to mating any other signals. Extra pins are provided for implementation of enclosure services and PCI Express (PCIe) sidebands.

Care needs to be taken in the application of this drive so that excessive stress is not exerted on the connector. Backplane configurations should pay particular attention so that the connector is not damaged due to excessive side loading, compressive forces, or from supporting the weight of the device.

Threaded holes on the form factor shall include a lead in feature. Exact configuration of the lead in is not defined since the implementation of the form factor is beyond the scope of this specification. An example lead in for a cast aluminum implementation is a countersink of 3.75 mm diameter x 90° (0.138" diameter x 90°). Appropriate information regarding recommended screw type and torque should be included in the product data sheet to enable proper mounting of the device without damaging threads.

Table 3-1 defines the dimensions associated with the form factor as illustrated in Figure 3-1 and the positioning of the X8 version of the SFF-8631 connector as illustrated in Figure 3-2.

Threaded holes on the form factor shall include a lead in feature. Exact configuration of the lead in is not defined since the implementation of the form factor is beyond the scope of this specification. An example lead in for a cast aluminum implementation is a countersink of 3.75 mm diameter x 90° (0.138" diameter x 90°). Appropriate information regarding recommended screw type and torque should be included in the product data sheet to enable proper mounting of the device without damaging threads.

TABLE 3-1 2.5" FORM FACTOR DRIVE WITH SFF-8631 CONNECTOR DIMENSIONS

Dimension	Millimeters	Inches	Comments
A1	15.00	0.591	Height
A2	100.45	3.955	Length
A3	69.85	2.750	Width
A4	0.25	0.010	Tolerance
A5	14.00	0.551	Mounting hole location
A6	90.60	3.567	Mounting hole location
A7	3.00	0.118	Mounting hole location
A8	34.62	1.363	Horizontal keepout location
A9	53.50	2.106	Minimum keepout width
A11	7.90	0.311	Minimum keepout height
A14	6.60	0.260	Minimum keepout depth
A17	0.25	0.010	Position tolerance
A18	6.00	0.236	Width mounting surface
A22	14.47	0.570	Connector horizontal location
A23	0.15	0.005	Connector vertical location
A24	7.15	0.281	Connector depth location
A25	3.10	0.122	Connector guide feature defining Datum B (see SFF-8631)
A26	48.10	1.894	Connector width (see SFF-8631)
A27	1.60	0.063	Connector tongue thickness (see SFF-8631)
A28	0.25	0.010	Parallelism
A29	0.50	0.020	Surface profile
A30	0.40	0.016	Perpendicularity
A31	0.00	0.000	Tolerance
A32	0.30	0.012	Tolerance
Threads			
A19	M 3		Thread size
A20	3.00	0.118	Maximum fastener penetration
Notes:			
1. Datums A and B are connector datums (see SFF-8631). Datum C is defined by this specification to locate the connector on the form factor and does not correlate with SFF-8631 Datum C.			
2. Datums W, X, Y, and Z are form factor datums.			
3. Threaded holes A19 shall include a lead in feature.			
4. Dimension A20 applies to fasteners used to mount the device. The device shall accept the maximum fastener penetration.			




FIGURE 3-1 2.5" FORM FACTOR DRIVE WITH SFF-8631 CONNECTOR




FIGURE 3-2 SFF-8631 CONNECTOR LOCATION DETAILS ON THE 2.5" FORM FACTOR